

## WATER- AND OIL-REPELLENT PROTECTION

**POLISHED PORCELAIN TILES, MARBLE AND GRANITE, STONE AND AGGLOMERATES**



MP90, a breathable oil- and water-repellent protective agent, prevents the absorption of oily or greasy substances (oil, soap, shampoo, etc.) and water on surfaces, preserving their original appearance.



### COVERAGE

#### APPROXIMATE COVERAGE (1 litre):

Marble/Granite	30 m <sup>2</sup>
porcelain tiles	30/40 m <sup>2</sup>
Terrazzo	30 m <sup>2</sup>

“Coverage shown is for guidance purposes only and refers to single coats”

#### Packaging

375 ml: boxes of 12.  
1 litre: boxes of 6.  
5 litres: boxes of 4.

#### WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- Ventilate the premises well during use and while the product is drying.
- Does not protect against acidic aggression.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.

#### TEMPERATURES

Storage temperature: from 0° to 30°C.  
The product should be applied to materials with temperature between 5° and 30°C.

### WHAT IT'S FOR

- The best stain-proofing product for porcelain tiles, marble and granite.
- It offers an anti-graffiti treatment for vertical natural stone surfaces.
- It is ideally suited for protecting kitchen and bathroom tops.
- Stain-proofing: it hampers the absorption of common watery and oily stains.

### ADVANTAGES

- Does not change the natural colour of surfaces.
- Does not form surface film.
- Treated surfaces are safe for food contact
- Impregnates, protects, and makes cleaning easier.
- It waterproofs, protects and facilitates cleaning.
- Ideal for the protection of crackle glazed tiles.
- An **A+** classified product in accordance with the French VOC regulation

### HOW TO USE IT

**No dilution required:** ready to use.

**Application:** Apply **MP90** evenly and continuously on a clean and dry surface using a brush, wetting the grout lines as well. Before the product dries completely (after roughly 10 - 15 minutes), rub the surface and remove any residues using a microfibre cloth wetted with the product. Dry the surface with a clean cloth. To speed up the process, it is possible to treat the surface with a single-disc floor scrubber. On highly absorbent materials, apply two coats of the product with an 8-hour interval in between. The surface can be walked on after 12 hours while the water- and oil-repellent protection becomes effective after 24 hours.

**Maintenance:** use a diluted solution of **CLEANER PRO**.

#### Caution:

*Before applying to the entire surface, test the product on a small area to check for colour changes.*

*Do not apply the product externally if rain is forecast.*

*Warning: ventilate the premises well during use and while the product is drying.*

*Does not protect against acidic aggression.*